

MS2000



The MS2000 is designed to mount in the bed of utility vehicles and work trucks. This versatile unit features an integral auger tube for accurately calibrating the flow of materials, from fertilizer to top dressing sand. Plus, it comes with a dual variable-speed control with digital readout for precise application and easy operation.

Features:

- For use with fertilizers, herbicides, pesticides, grass seed, or as a top dresser
- 11.0 cu ft capacity
- Up to 30 ft spread width
- Fitted top screen, fitted hopper cover and vibrator
- Full 2 year warranty
- Completely electric powered
- Quick connect spinner assembly

Applications:

- Colleges & universities
- Hospitals & healthcare facilities
- Parks & recreation / grounds care
- Athletic fields, stadiums
- Golf courses



Dual Variable Speed Control



Adjustable Stainless Steel Spinner with Cupped Fins



MS2000

MS2000

EMPTY WEIGHT:	280 lbs. (127.0 kg)
OVERALL LENGTH:	64" (163.0 cm)
OVERALL WIDTH:	48.5" (123.2 cm)
OVERALL HEIGHT:	27" (68.6 cm)
CAPACITY:	11 cu ft (0.31 cu m)
SPREADING WIDTH:	Up to 30 ft (9.1 m)
HOPPER:	Anti-corrosive polyethylene
BED LENGTH:	45" (114.0 kg)